


- 12.1" TFT Display
- 65536 True Color TFT LCD
- 32 Bit, 520 MHz RISC CPU
- 16 MB FLASH + 32 MB SDRAM
- 512 KB Recipe Memory, Record Date Easily
- Real-Time Clock, Reserve Time for More than 2 Years at Power Off State
- 3 COM Port, Supports Simultaneous Communications;RS232/RS422/RS485
- Input Voltage Range 21~28VDC



The MT5000 Series is a very powerful HMI product that will make your application soar. This HMI line come with a 65536 color display mode that gives your touch screen rich color and incomparable resolution. With the application of a powerful 520 MHz 32-bit RISC processor, the MT5000 provides faster processing speeds. Each HMI supports simultaneous communications via its multiple serial ports, so that you may connect to different controllers at the same time. With the simple, convenient and powerful HMIware configuration software, the user can master its design method and create first-class programs efficiently.



L011278

Performance Specification	
Display	12.1" TFT
Resolution	800 x 600 Pixels
Color	65,536 Colors
Backlight	2 CCFL
Brightness	250 cd/m ²
Backlight Life	50,000 Hrs
Touch Panel	4-Wire Precision Resistance Network
Processor	32-bit RISC CPU 520 MHz
Memory	16 MB FLASH, 32 MB SDRAM
Expandable Memory	2 USB Hosts, 1 SD Card
Recipe Memory & RTC	512 KB & RTC
Printer Port	USB/Serial Port
Ethernet	10/100 Base-T
Audio Interface	1 Audio Output Interface
Video Interface	2 PAL Video Input, BNC Connector
Program Download	USB Slave/Serial Port/Ethernet Port
COM Port	COM0:RS232/RS485-2/RS485-4, COM1:RS232/RS485-2/RS485-4, COM0:RS232
Expansion Port	None
Electrical Specification	
Rated Power	15.6 W
Rated Voltage	24 VDC
Input Range	21~28 VDC
Power Down Allowed	< 3ms
Insulation Resistance	> 50M Ω @ 500 VDC
Dielectric Strength Test	500 VAC 1 Minute
Structure Specification	
Shell Color	Black
Shell Material	Metal
Dimensions(mm)	350 x 264 x 48.7
Cutout Size(mm)	327 x 241
Weight	4.3 Kg
Environment Specification	
Operating Temperature	-10°~60° C
Operating Humidity	10~90% Non-Condensing
Storage Temperature	-20°~70° C
Storage Humidity	10~90% Non-Condensing
Shockproof Test	10~25Hz (X,Y,Z Direction, 2G, 30 Minutes)
Cooling Method	Natural Air Cooling
Certification	
Degree of Protection	IP65 (Front Panel)
CE Certification	Comply with EN61000-6-2:2005 and EN61000-6-4:2007 Standards
FCC Compatibility	Complies with FCC Class A